# QUART HEALTHCARE INC. DynaLAL III Low Air Loss Mattress Replacement System





The DynaLAL III mattress replacement system combines 3:1 alternating and true low air loss features for the prevention and treatment of pressure ulcers.

With multiple pressure reduction features, simplicity of functional control, quick-disconnect components design, the DynaLAL III Mattress Replacement System effectively manages ulcers and pain.

## **NEW FEATURES**

Pulsation Therapy Fowler Pressure Function Auto-Sensor and Adjustment Technology Bariatric Function

#### **True Low Air loss Technology**

72 openings on the air cells, constant air distributes equally under a vapour-permeable cover.

## **Deep Cell 3:1 Alternation Therapy**

18 independent 8 inch high cells inflate and deflate in a 3:1 cycle, creating maximum support for the individual using 2/3 of the air cells.

#### **Comfort Levels**

16 comfort levels for different weight ranges.

#### **Pulsation Mode**

Pressure in the cells will pulsate in an alternating 3:1 pattern without complete offload.

# **Auto Firm**

Quickly inflates the mattress with a simple push of a button for rapid installation and nursing care requirements.

# **Visual and Audio Alarms**

Sensor Disconnect / Leaving Bed / Bottoming Out (Alarms can be silenced)

# **CPR Quick-Release**

Deflates the torso section in less than 30 seconds in the event of medical emergencies. Disconnect air hose set from control unit.

# **Specifications**

Mattress		Control Unit	
Weight restrictions	Up to 1000 lbs	Inflation Time	under 2 minutes
Inflated Dimensions	36" x 80" x 10" part # SY-QHI0002-DY 48" x 80" x 10" part # SY-QHI0006-DY	Functions	Alternating pressure (5 - 20 min) 16 comfort levels; Auto firm; Static mode Lock-out Capability Auto-memory Reset Low Air Loss
Weight	37 lbs ( 36" wide) / 42 lbs ( 48" wide )	Power requirement	AC 110 - 120 volt, 60Hz, 5 Amp
Air Cell Material	Polyurethane	Size	7.5"(L) x 11"(W) x 13"(H)
Cover Material	Quilted fabric with polyurethane coating	Weight	12 lbs
Base Material	Woven Polyester fabric with PVC backing	Max. Air-flow	1200 lpm
Safety Standard	Meets open flame requirements (FCC 16 CFR 1633)	Safety Standard	UL/cUL

www.quarthealthcare.com

e-mail: sales@quarthealthcare.com